HOSHIZAKI



VIEW B(1/10)　　VIEW A(1/10)

1 PLUG SHAPE



BASKET DETAILS







ITEM	Hoshizaki Deep Freezer
MODEL	HDF−400A−SEA
POWER SUPPLY	1 Phase 220−240V 50Hz　Capacity: 1.14kVA (4.8A)
AMPERAGE	Running: 2.2A　Rated Motor: 2.2A Starting: 18A
ELECTRIC CONSUMPTION	330W (Power Factor: 62%)
HEAT REJECTION	560W
POWER CORD	2.8m (with Earth Wire, UK Plug)
EFFECTIVE CAPACITY	385L
OUTSIDE DIMENSIONS	1565mm(W) x 710mm(D) x 875mm(H)
INSIDE DIMENSIONS	1400mm(W) x 440mm(D) x 685mm(H)
EXTERIOR	Painted Steel (Off−White)
INTERIOR	Painted Steel (Off−White)
DOOR	Horizontally Hinged Single Door + Stainless Steel
INSULATION	Polyurethane Foam
REFRIGERATION SYSTEM	Convection Cooling
COMPRESSOR	Hermetic 551W
CONDENSER	Tube on Sheet Built in Exterior Cabinet + Wire on Tube
EVAPORATOR	Tube on Sheet Built in Interior Cabinet
REFRIGERANT	R600・R1150
TEMPERATURE CONTROL	Microprocessor (Digital Temp Indication) Adjustable from −60 to −50°C
ELECTRIC CIRCUIT PROTECTION	10A Fuse, Earth Wire
REFRIGERANT CIRCUIT PROTECTION	Motor Protector (Auto−reset)
LEG	Plastic
LOCK	Rotating Lock (Key x 2)
WEIGHT	94kg (Gross Approx. 104kg)
PACKAGE	Carton 1625mm(W) x 775mm(D) x 964mm(H)
ACCESSORIES	Basket x 3, Separator, Scraper
OPERATING CONDITIONS	Ambient Temperature: 5 − 32°C Voltage Range: Rated Voltage ±6%

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 30°C.
3. Allow at least 100mm extra space at both sides, 150mm at the rear, and 1000mm at the top of the unit for proper exhaust.
   The hatched area shows the wall and ceiling.
4. The main breaker capacity is 15A.
   Be sure to use an exclusive circuit
   (with overload & short circuit protection).
5. Product code: V115−D001

HOSHIZAKI DEEP FREEZER HDF−400A−SEA

APPROVED	CHECKED	DESIGNED	DRAWN	SCALE	
NAGASAWA	NAGASE	TAMURA	NISHIKOORI	1/20	TRIGONOMETRY

NAGASAWA	TAMURA	1	2024.08.21	DATE 2024.06.13	DRAWING NO. D38629	SYMBOL 1
APPROVED	DESIGNED	SYMBOL	DATE			

000520
施行